



EN 14592:2018+A1:2012



L. Künzel Nagelfabrik GmbH



Certificate

Circular ring shank Coil nails for structural timber products Diameter = 3,1mm Length = 65 - 98 mm

Properties of the material used:

- non alloy low carbon steel, galvanized
- tensile strength in accordance with EN 10218-1, min. 850 N/mm²

Characteristic mechanical properties:

- Characteristic yield moment: $M_{y,k} = 3760 \text{ Nmm}$
- Characteristic withdrawal parameter:
referred to wood with a characteristic density not less than 422 kg/m³ $f_{ax,k} = 2,1 \text{ N/mm}^2$
- Characteristic Head pull-through parameter:
referred to wood with a characteristic density not less than 422 kg/m³ $f_{head,k} = 23,7 \text{ N/mm}^2$
- Characteristic tensile capacity: $f_{tens,k} = 3,6 \text{ kN}$

Durability (Corrosion Protection):

Bright - Service Class 1 or
Galv < 12 ym Service Class 1 or
Galv 12 ym Service Class 2 acc. to EN1995-1-1

On the basis of the obtained test results presented in this Report, in the agreed scope, in accordance with the requirements of the standard **EN 14592:2018 +A1:2012** Table 2, an ASSESSMENT OF PERFORMANCE was prepared for the tested product.